

MEANS FOR HOLDING TWO PIECES IN POSITION RELATIVE TO EACH
OTHER

The present invention relates to means for holding two pieces in position for fixing them together. Such position-holding means can be used, for example, to interlock two tools, or a tool and a tool support.

u. In assembly lines for motor vehicle bodywork, subassemblies (such as the subframe, the sides of the body, the rear panel, ...) are put into position relative to one another and relative to welding robots. Since bodywork pieces are naturally deformable when subjected to stresses, the tooling used for making bodywork of determined and reproducible shape performs two functions: firstly it constitutes reinforcement for each of the deformable subassemblies so as to stiffen them, and secondly it constitutes a stable interface providing accurate positioning in a fixed frame of reference defined relative to the welding robots.

In a recently developed method of building motor vehicle bodies, the step of assembling the bodywork includes a stage of putting two body sides and a rear panel into place and ~~holding them~~ in position in the frame of reference of the assembly station by means of two parallel side tools each co-operating with one of the sides of the body and by means of a transverse tool co-operating with the rear panel, the three tools being connected to one another and to the frame of reference of the assembly station in such a manner that the transverse tool is placed and held in said frame of reference in a position that is precise and locked, and in such a manner that it forms a spacing and bracing tool for the two tools that are parallel in a direction perpendicular thereto.

Depending on the type of body to be assembled, it is
35 necessary either for the rear panel to be put into place
initially so that the sides of the body can then come up
on either side thereof, or else for the sides of the body

[illegible]

to be put into place initially so that the rear panel can then be fitted over the corresponding ends thereof. In addition, in order to increase productivity, it can be advantageous for the three tools to be capable of engaging or disengaging mutually relative to one another simultaneously so as to save time. Unfortunately, known means for holding two pieces in position relative to each other allow for only one direction in which said pieces can be engaged relative to each other such that incorporating such means in the above-described assembly station for interconnecting the tools would require the tools to be put into place successively at least to some extent and in a predetermined order. That limits the flexibility and the maximum productivity of the method.

15 The invention proposes means that are simple for holding two pieces in position while enabling the pieces to be brought towards each other in at least two extreme coplanar docking directions that form a docking angle between them.

20 According to the invention, the position-holding means comprises firstly at least a male and a female V each provided with means for fixing to a respective one of the pieces so that each V is centered substantially on a direction parallel to the bisector of the docking angle, the female V possessing an inlet portion having an aperture angle not less than the docking angle, and secondly means for pressing the male V against the female V along said bisector.

30 Thus, each V provides a function of guiding and/or recentering the other V during the stage in which the two pieces are approaching each other, thus enabling the axes of the Vs to be brought into alignment, and a function of statically positioning the other V once the pieces have approached each other and are held in position by the means pressing the Vs against each other.

35 According to a first particular characteristic, the Vs have aperture angles that are substantially equal and

greater than the docking about and, more particularly, for a docking angle of about 90° , the aperture angles of the Vs are equal to about 120° . Since the aperture angle of the Vs is greater than the docking angle,

5 uncertainties in the relative positioning of the Vs prior to coming into contact are of no consequence. This is particularly advantageous when the pieces are put into place by standard robots of medium positioning accuracy.

10 According to a second particular characteristic, the female V possesses an end portion having an aperture angle substantially equal to the aperture angle of the male V which is not less than the docking angle, and the aperture angle of the inlet portion of the female V is greater than the aperture angle of the end portion
15 thereof and, more particularly, for a docking angle substantially equal to 90° , the aperture angle of the male V and of the end portion of the female V is substantially equal to 90° , and the aperture angle of the inlet portion of the female V is substantially equal to
20 120° .

25 In a particular embodiment, the means for pressing the Vs together comprise a peg projecting from the male V symmetrically relative thereto so as to be inserted into an elongate slot formed in the female V and having a major axis contained in the plane of the docking
30 direction, at least one jaw being movably mounted on the peg to be actuated between an active position in which it forms an abutment for a rear face of the female V facing away from the male V, and an inactive position in which it is retracted and allows the peg to pass freely through the slot of the female V. The structure of the position-
35 holding means is thus compact and relatively simple.

40 The present invention also provides apparatus for assembling bodywork, the apparatus comprising two side tools for supporting the body sides, a tool extending transversely relative to said two side tools, and means presenting one of the above-specified characteristics for

holding the side tools and the transverse tool in position relative to one another, the transverse tool having at least two Vs disposed symmetrically about a longitudinal axis of the bodywork and designed to co-operate with corresponding Vs fixed to the side tools.

Other characteristics and advantages of the invention will appear on reading the following description of particular, non-limiting embodiments of the invention.

Reference is made to the accompanying drawings, in which:

- Figure 1 is a diagrammatic perspective view of apparatus in accordance with the invention for assembling vehicle bodywork;

- Figure 2 is a fragmentary plan view showing a first mode of bringing together tools of the apparatus of the invention;

- Figure 3 is a view analogous to Figure 2 showing a second mode of bringing the tools together;

- Figure 4 is a perspective view of means for holding two tools in position, the means being shown while they are being brought together;

- Figure 5 is a fragmentary section through two tools held in position relative to each other;

- Figures 6 and 7 are a face view and a side view of a variant embodiment of the male V of the apparatus of the invention; and

- Figures 8 and 9 are views analogous to Figures 6 and 7 showing the corresponding variant embodiment of the female V.

The apparatus of the invention is for use in assembling vehicle bodywork comprising a subframe 1 of the vehicle body, two body sides 2, and a rear panel 3.

With reference to Figure 1, the assembly apparatus comprises a fixed structure 10 possessing an X, Y, Z frame of reference. A support for the subframe 1 of the motor vehicle body can be brought into this structure in

such a manner that the longitudinal axis 1' of the subframe 1 is parallel to the X direction. The means for bringing this support into the structure and putting it into position in the frame of reference are known in themselves and they are not shown. By way of example, the support can be constituted by a pallet which travels on a conveyor passing through the structure 10 along the X direction, with lifting means being provided in the structure to separate the pallet from the conveyor and put it into a reference position in the X, Y, Z frame.

The assembly apparatus comprises a transverse tool for co-operating with the panel 3 and two side tools for co-operating with the body sides 2.

The transverse tool is symbolized as a frame 11 extending transversely to the direction X and suitable for being coupled to the structure 10 via support studs 12, for example. In this case, the studs 12 co-operate with the frame 11 via four fixing points which enable the frame 11 to be held completely stationary in the structure 10 both in translation relative to the directions X, Y, and Z and in rotation about them. In this case, the frame 11 is fitted on one of its faces with gripping and handling means for use by a robot 13 handling the frame. On its other face, the frame 11 possesses clamps for co-operating with the panel 3.

The side tools are symbolized as frames 14 extending parallel to the Z direction and supported by the structure 10 via studs 15 which serve to fix the positions of the frames in the Z direction. Each frame 14 is fitted on one of its faces with gripping and handling means for engaging a robot 16 that handles it, and on its other face with clamps for co-operating with the corresponding body side 2.

The rear upright 17 of each frame 14 is connected to the frame 11 via position-holding means given overall reference 18 for holding the frames 14 in a vertical position that is spaced and braced by the frame 11, and

5

10

15

25

35

docking angle, i.e., in this case, the bisector \underline{b} of the aperture angle α of a female V forms an angle of about 45° with the X and Y directions and is coplanar therewith. An elongate slot 22 having a major axis 22' contained in the plane of the docking directions is formed transversely in each female V 20.

Each position-holding means 18 also includes means for pressing the male V 19 against the female V 20 along the bisector of the docking angle β and the bisector \underline{b} of the aperture angles α .

This means comprises a peg 23 projecting from the male V 19 along the bisector \underline{b} , symmetrically about the bisector, and parallel to the bisector of the docking angle. Two jaws 24 are movably mounted on the peg 23 to be actuated in conventional manner by a control rod 25 (formed by the rod of an actuator that is not shown) to move between an active position in which they project laterally from the peg 23 (Figure 5) and an inactive position in which they are retracted into the peg 23 (Figure 4).

In operation, the frames 11 and 14 and the corresponding bodywork elements 3 and 2 can be caused to co-operate at the time when the frames 11 and 14 are put into place in the structure 10 of the station, the panel 3, the subframe 1, and the body side 2 previously put into place in the structure of the apparatus then being preassembled. The clamps of the frames 11 and 14 can also constitute means for coupling the frame 11, 14 with the corresponding bodywork elements 3, 2 that are put into operation outside the assembly line, in which case the frame 11, 14 constitutes a kind of pallet for transporting the corresponding bodywork element 3, 2 and the robot 13, 16 serves to put the pallet into place in the apparatus.

In a first mode of docking the tools together as shown in Figure 2 and corresponding to bodywork of a type in which the body sides 2 are brought up to the panel 3,

the frame 11 is put into place in the structure 10 before the frames 14, and these frames are subsequently brought up to the frame 11 along the direction D1 parallel to the Y direction.

5 In a second docking mode shown in Figure 3 and corresponding to bodywork of a type in which the panel 3 is brought up against the rear ends of the body sides 2, the frames 14 are put into place in the structure 10 before the frame 11, which frame is then brought up to the frames 14 along the direction D2 parallel to the X direction.

In a third docking mode, the frames 11 and 14 are moved towards one another simultaneously.

During the docking stage, the peg 23 of each means 15 18 is inserted into the slot 22 of the corresponding female V 20 and moved along the slot until the male V 19 is received in the female V 20. The jaws 24 are moved into their active positions so that they bear against the rear face 26 of the female V 20 in which the male V 19 is engaged, thereby applying traction force on the male V 19 which is pressed against the female V 20 in a direction parallel to the bisector b of the aperture angle α of the Vs (see Figure 5), thus forming an abutment for the rear face 26. It will be observed that the aperture angle α 20 of the Vs and the materials used for making the Vs (in this case steel) are determined in such a manner as to enable the contacting faces of each V to slide over one another during the stages of docking the Vs and pressing them one against another. The angle between the normal 25 to these faces and the direction in which the force pressing the Vs against one another is applied is thus greater than the friction angle of the materials used for making the Vs.

The rear portions of the body sides 2 and the panel 35 3 are thus accurately positioned relative to the subframe 1 and this is done in a manner that is very rigid using means that are simple and lightweight.

5

10

25

30

35

It should be observed that the male V 19 has two opposite transverse parallel faces 27 and that the female V has two transverse parallel faces 28 facing each other

on either side of the slot 22. When the Vs are mounted on the corresponding tools, the faces 27 and 28 are perpendicular to the Z direction such that when the male V 19 is pressed against the female V 20 the faces 28
5 bracket the faces 27 so as to prevent the male and female Vs from moving relative to each other in the Z direction. This serves to provide relative positioning of the tools in the Z direction.

Naturally, the invention is not limited to the
10 embodiment described and various embodiments can be provided without going beyond the ambit of the invention as defined by the claims.

In particular, the position-holding means can include additional male and female Vs for providing
15 relative positioning of the tools in the Z direction, or the male and females Vs can have conical portions.

In addition, different aperture angles can be used for the Vs, such angles being determined in particular as a function of the magnitude of the docking angle.

It is also possible to provide for the transverse
20 tool of the assembly apparatus not to co-operate with any bodywork element and to perform solely the function of spacing and bracing the side tools.

Finally, the position-holding means of the invention
25 is not limited to the application described relating to the assembly apparatus, and can be employed for holding in position any type of piece that is being handled, in particular pieces that are handled by robots in order to be moved towards each other along two extreme docking
30 directions.